

DOPPIA II 9075

FEATURES

- Compact powerful (138dB peak SPL@ 1m) enclosure for bi/tri-amping, with two 12" (LF) woofers in hybrid reflex/band-pass configuration, a 10" midrange and a 3" diaphragm HF compression driver, the first wave guide loaded, the second horn loaded; ferrofluid cooled HF section voice coil.
- Modular system with interchangeable components for the utmost flexibility to satisfy different acoustic coverage requirements. Can be used along with other units of the same type in array configuration.
- Extremely linear phase response of within $\pm 50^\circ$ from 400Hz to 20kHz.
- Biamping or triamping and control via dedicated digital processor.
- Also available in "P" version with built-in crossover for passive biamping of the MF and HF sections, consequently saving an amplifier compared with the triamped "A" version.
- Cabinet reinforced internally for the utmost sturdiness, eliminating coloration due to resonance. Equipped with Outline's proprietary "Fast Hanger" system for fast reasonably priced flying.

APPLICATIONS

- Medium/short throw system. A few units are ideal for live use in no-nonsense applications at medium sized concerts, with groups, bands and orchestras.
- Permanent high quality installations in theatres, clubs, indoor sports arenas, ideal for use along with Outline subwoofers for further extension of the low end and therefore an increase in dynamics.

DESCRIPTION

Doppia II 9075 is a professional full range 3-way loudspeaker system, in version "A" for triamping or version "P" for biamping with passive low-loss crossover built in for the mid/high frequency section. It comprises a low frequency section using two 12" loudspeakers in hybrid reflex/band-pass configuration, a mid section with a high efficiency 10" loudspeaker loaded by a symmetric wave guide with a square mouth and low compression ratio and low distortion and a high frequency section using a compression driver with a 2" throat and 3" titanium diaphragm with overload protection, loaded by an asymmetric controlled directivity horn which also has a square mouth and can be turned through 90° on its axis inside the cabinet in order to change the horizontal/vertical dispersion. The acoustic reproduced bandwidth is 60.5Hz-19.7kHz at -10dB, with a great linearity of within ± 3 dB from 77Hz to 18.9kHz, for the reproduction of many types of applications. When triamplified, the system has high sensitivity for the low section 102dB SPL at 1m, 107dB SPL at 1m for the mid section and over 109dB SPL at 1m for the HF section. Driven at maximum peak power, each section is able to produce a maximum peak of 134dB SPL (low), 138dB SPL (mid) and 137dB SPL (high) at 1m. The maximum allowed power for each section is 400 Watt AES (1,600 peak) for basses, 300 Watt AES (1,200 peak) for midrange and 150 Watt AES (600 peak) for high. Average dispersion from 500Hz to 4kHz is 100° horizontal and 100° vertical, from 500 Hz to 10,000 Hz is 100° horizontal and 90° vertical for short and medium throw applications. The trapezoidal cabinet is built in high quality 15mm baltic plywood, strengthened by the complex internal structure and suitably positioned internal bracing to eliminate any resonance of the cabinet's sides. The black outer finish is in high quality scratch-resistant paint. The cabinet has 6 fast flying points, that makes vertical or horizontal hanging extremely easy and reliable, by using the appropriate optional accessories. The front of the enclosure has recessed sockets for fitting an optional trolley, for handling and protecting the fibreglass wave guides during transport. Six recessed integrated handles in the side panels of the cabinet are used for a positive grip during handling.



TECHNICAL SPECIFICATIONS:

FREQUENCY RESPONSE	(-10 dB) (± 3 dB)	60.5 Hz \div 19.7 kHz 77 Hz \div 18.9 kHz
AVERAGE DISPERSION	>5 kHz	$90^\circ \times 80^\circ$ (H x V)
IMPEDANCE (Ω)	Low (min) Mid (min) High (min)	8 (8.5 @ 187 Hz) 8 (8 @ 262 Hz) 16 (10.8 @ 5450 Hz)
MAX SENSITIVITY (dB SPL @ 1W 1m)	Low Mid High	105 (Half-space) 107 109.5
POWER - WATT AES	Cont. Low Mid High	Peak 400 1600 300 1200 150 600
MAX SPL @ 1 m (calculated)	Cont. Low Mid Hi	Peak 131 137 (Half-space) 132 138 131 137

CONNECTORS (active version)	2 x NL8 Speakon in parallel: Low Pin 1 + pos ; Pin 1 - neg Mid Pin 3 + pos ; Pin 3 - neg High Pin 4 + pos ; Pin 4 - neg
------------------------------------	--

LOUDSPEAKERS AND LOADING	Low: 2 x 12" Hybrid loading Vented Box Mid: 1 x 10" Wave Guide loaded High: 1 x 2" Exit (3" diaphragm), Wave Guide loaded
---------------------------------	---

WEIGHT	Single unit Shipping (1 unit)
	55 kg (121.3 lb) 62 kg (136.7 lb)

DIMENSIONS	
Height	74 cm (29.1") 82 cm (32.3")
Width	55 cm (21.7") 63 cm (24.8")
Depth	60 cm (23.6") 67 cm (26.4")

POINT SOURCE SYSTEMS