

IS6T

FEATURES

- Extremely compact enclosures
- Accurately sound reproduction
- Fast and secure mounting arrangement
- 100V transformers included (15/30 W or by-pass position)
- Available in black or white colours

APPLICATIONS

- Multimedia Facilities, Presentation Suites Boardrooms
- Lecture Halls Theme Venues
- Music-Restaurants, Dance&dinner clubs
- Show-rooms Shopping malls
- Fitness & wellness centres

DESCRIPTION

The IS6T are high fidelity, full range two-way loudspeakers mounted in a plastic sealed box and designed for use in wide variety in room installation. IS6T features a 6.5" (16.5 cm) LF cone driver with a Neodymium HF section. They both employs an optimized passive crossover with 1st order acoustic slopes to integrate both the on-axis and off-axis (power response) characteristics of the HF and LF sections. A 100V transformer is integrated within both the cabinets and a multitap switch for low impedance use enables the users to choose 15W, 30W or by-pass position.



TECHNICAL SPECIFICATIONS:

FREQUENCY RESPONSE

IS6T (±5 dB) 110 Hz ÷ 20 kHz

IMPEDANCE (Ω)

IS6T 8

MAX SENSITIVITY (dB SPL @ 1W 1m)

IS6T 90

POWER - WATT MAX

IS6T 100

MAX SPL @ 1 m (calculated)

IS6T 113 Peak

COMPONENTS AND LOADING

IS6T Low 6.5" cone driver
High 19 mm Neodymium transducer

ACCESSORIES INCLUDED

IS6T Bracket, 100V transformer (15/30W/ by- pass)

WEIGHT

IS6T 4.2 kg (9.3 lb) (each)

DIMENSIONS

Height 28.0 cm (11.0")
Width 19.0 cm (7.5")
Depth 17.0 cm (6.7")

INSTALLATION SERIES